ViewSonic[®] PJ862 Projector

VALUE, RELIABILITY, PERFORMANCE



High-performance, high-brightness projector.

The ViewSonic PJ862 raises the bar for performance, features and reliability. The PJ862 is a full-function multimedia projector that delivers native XGA 1024x768 RESOLUTION and ULTRA-BRIGHT 3,100 LUMENS. Multiple inputs including DVI-HDCP, component, composite and S-video, connect to a variety of display sources. Advanced features such as progressive scan, 3:2

pull down, auto keystone correction, and zoom lens PRESENT A PERFECT IMAGE IN VIRTUALLY ANY SETTING. The PJ862 is powerful enough for dynamic professional presentations and portable enough to take home with you to enjoy your favorite movie.

ViewSonic® has the best warranty and service support in the business!

3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

Multimedia projector for any situation.

- ••• Bright in virtually any setting with 3,100 lumens

 Packs 3,100 lumens in just 8.8 lbs. It's the bright choice for the mobile professional.
- ··· Ultimate video source flexibility

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.



Easy-to-use remote with laser included.

- ••• Supports HD signals including 720p and 1080i
 Capable of displaying HDTV signals as well as other video and data sources*.

Progressive scan and 3:2 pull down for superior video performance.

- ••• Whisper-mode extends lamp life

 Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- ··· The perfect image in any setting

Use the one touch setup button and auto vertical keystone correction to set up quickly.



··· The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty. ***







the choice of professionals

ViewSonic® PJ862 Projector VALUE, RELIABILITY, PERFORMANCE







- 1. Stand by/on
- 3. Kensington security port
- 4. Dual RGB inputs and RGB output, DVI, RS-232, RJ-45
- 5. Component, composite, and S-video input
- 6. Zoom and focus rings

PJ862 Distance Calculator				
Image Size (Diagonal in)	Height (in.)	Width (in.)	Throw Distance	
40 60 100 150 200 250 300	24 36 60 90 120 150	32 48 80 120 160 200 240	47 - 57 71 - 86 120 - 144 181 - 217 241 - 291 302 - 364 363 - 437	

Throw ratio: 1.49~1.79:1 (distance:width) Accuracy of the calculations are +/- 5%. For additional calculations visit Viewsonic.com.

Optional Accessories

· Universal ceiling mount kit

 Replacement lamp 	RLC-003
 Hard case with wheels 	PRJ-HCA-002
 Stackable ATA hard shipping case 	CASE-003
• Extended Express Exchange®	PRJ-EE-05-03

PORTABLE PROJECTOR

IONIADLLIN	OJECTOR	
	Type Pixel Format Lens Zoom Factor Keystone	0.79" Poly–Si TFT with micro-lens 1024x768 XGA (native resolution) Manual zoom/focus 1.2 Vertical ± 15°, horizontal ± 15°
DISPLAY	Size Throw Distance Lamp Brightness Contrast Ratio Aspect Ratio	30"-300" (diagonally) 2.95'-36.09' (wide) 230W, 2,000 hours** 3,100 lumens 400:1 4:3, 16:9
AUDIO	Speakers	4x3 watts
INPUT SIGNAL	Video Frequency	RGB analog, NTSCM, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i) F _h : 15–91kHz; F _v : 56–120Hz
COMPATIBILITY	PC Mac ^{®††}	Analog: from VGA up to UXGA (scaled) Analog: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input/output) DVI (input) Composite Video (input) S-Video (input) Component Video (input) Audio (input) Audio (output) USB (output) Control Network Connector	Mini-Din 4-pin (x1)
POWER	Voltage Consumption	100–240 VAC, 50–60Hz (universal) 370 watts (typ)
CONTROLS	Physical OnView®	Standby, menu, input, reset, H/V keystone Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, V. position, H. position, H. Phase, H. size, auto adjust, execute, video menu, setup menu, screen menu, option menu, network menu, color space, component, video format, frame lock, information, keystone, whisper, mirror, volume, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, auto search, auto power off, auto power on, lamp time, filter time, service menu 32–95°F (0–30° C)
CONDITIONS NOISE LEVEL	Humidity Normal	10–85% (non-condensing) 38 dB (typ)
NOISE LEVEL	Whisper mode	32 dB (typ)
DIMENSIONS (WxDxH)	Physical	13.2" x 3.7" x 10.4" 336mm x 95mm x 265mm
WEIGHT	Net/Gross	8.8 lb. (4.0 kg), 20.2 lb. (9.2 kg)
REGULATIONS		UL 60950, UL-DEMKO/GS, C-UL, FCC-B, CB, CE, C-TICK, NOM, TUV-S
OTHER		Auto vertical keystone correction, H/V digital keystone correction, progressive scan, 3:2 pull down, soft carrying case, remote with mouse control, dual RGB input, RGB output, auto adjust, stereo speakers
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year warranty on lamp.***



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

WMK-005

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life up to 4,000 hours. ***Three-year limited warranty and 1-year lamp warranty available in U.S. and Canada for current projector models purchased on or after May 1, 2002. Applies to manufacturer's installed lamp only. All accessory lamps purchased separately are warranted for 90 days. Subject to terms and conditions, verification and approval. For Express Exchange program details, visit ViewSonic.com. (Excludes U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Coppright © 2005 ViewSonic Corporation. All rights reserved. [12229-008-12/04] PI862-1